



DuraCoat
ASK THE EXPERTS

Duracoat Vinyl Silk Emulsion

Features

- Outstanding stain resistance
- Excellent Mar and Scuff resistance
- Provides mildew resistant coating
- Excellent flow and brushability

General Description

Duracoat Vinyl Silk Emulsion is designed to give a tough, durable sheen (silky) finish with outstanding washability. The paint film works to prevent stains from penetrating the surface and ensures easy cleanability.


Recommended for

Living rooms, bed rooms, dining rooms, kitchens, bathrooms, commercial applications where silky finish with highest performance characteristics are desired.

Limitations

Do not apply when the temperature is below 10°C.

Product Information

Product Information	
Colour Range : Available in a wide range of colors from Duracoat Color Chart, Duracoat Classic Fandeck and Duracoat Colour Plus Fandeck	Technical Data
	Finish Silky
Special Colors : Special colors can be made available on request	Spread Rate 12-14 m ² /l when applied on a smooth non porous surfaces
	Drying time - Surface dry 20-30 mins - Recoating time 3 hours
Pack sizes : 1ltr, 4 ltrs, 20 ltrs	Application By Brush, Rollers, Conventional Spray
Technical Assistance: If in doubt please contact our Technical department on 6823555/954	Thinning Up to 25% (Vol.) with water if applied by brush or roller. If applied by spray, more water may be needed to adjust to sprayable viscosity.
	Cleaning Clean all equipments with water. Spray equipment should be given a final rinse with Duracoat White Spirit to prevent rusting
 DuraCoat ECO FRIENDLY PAINT ASK THE EXPERTS <small>This product is environmentally friendly and has low VOC (volatile organic compounds)</small>	Volatile Organic Compounds (VOC) < 30 gm/l

Duracoat Vinyl Silk Emulsion

Surface Preparation

All surfaces to be painted must be clean, dry and free from dusts, grease or any loose material. Cracks and defects should be filled with appropriate crack filler followed by appropriate primer.

New Unpainted Cement or Plaster surfaces:

Apply one coat of Duracoat Universal Undercoat or Duracoat Emulsion Undercoat followed by 2-3 coats of Duracoat Vinyl Silk Emulsion.

Previously painted surface :

Clean the surface and remove loose, flaking and powdery materials. Apply one coat of Duracoat Universal Undercoat or Duracoat Emulsion Undercoat followed by 2-3 coats of Duracoat Vinyl Silk Emulsion

For smooth uniform finish use Duracoat Smotex Lite/Ekogips Satin plaster for skimming.

Precautions

- Ensure good ventilation during application and drying
- Store the product at ambient conditions in well ventilated locations and away from the source of ignition and fire
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persists seek medical advise
- Do not inhale or inject. In case of inhalation move to fresh air and seek medication attention if symptoms persists in both the cases.
- Use appropriate personal protective equipments.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould, etc before application of the paint system.

Application

- Stir thoroughly before and during use
- Always use good quality brush
- Try to paint in one motion
- Always pre test on a small area first

Note

- When over coating a dark shade with a light shade three coats may be required
- On dark shades like bright Reds, Greens, Oranges an additional coat will be required as some shades have low opacity

Post Application Instructions

The best thing to remove wall stains is to remove it immediately.

For removing stains, sponge clean with mild soap/detergent solution and wipe clean.

For better washability ensure the paint surface is cured for 1 week.

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

Refer to MSDS for additional health and safety information

Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. representative to obtain the most recent Product Data Information