



DuraCoat
ASK THE EXPERTS

Duracoat Duraplast

Features

- Easy clean up
- Easy application
- Excellent protection against UV attack
- Excellent anti algal performance
- Long lasting fresh appearance
- Self Priming

Recommended for

Interior / exterior residential & commercial applications where smooth matt finish with highest performance characteristics are desired.


General Description

Premium quality emulsion paint for application on internal or external walls of buildings. It contains a special fungicide that makes it potent to mould and algae. Duraplast is specially formulated to withstand extreme tropical conditions of high rainfall, humidity and heat.

Limitations

Do not apply when the temperature is below 10°C.

Product Information

Colour Range :	Technical Data*	White
Available in a wide range of colors from Duracoat Color Chart, Duracoat Classic Fandek and Duracoat Plus Fandek	Finish	-Matt to low sheen
	Spread Rate	-13-16 Sq. Mt./Ltr when applied on a smooth plaster
Special Colors :	Drying time	
Special colors can be made available on request	- Surface dry	-20-30 mins
	- Recoating time	-3-4 hours
Pack sizes : 1ltr, 4 ltrs, 20 ltrs	Application	-By Brush, Rollers, Conventional Spray
Technical Assistance: If in doubt please contact our Technical department on 82355/954	Thinning	-Up to 25% (Vol.) water if applied by brush or roller. If applied by spray, more water may be needed to adjust to spray able viscosity.
 DuraCoat ECO FRIENDLY PAINT <small>ASK THE EXPERTS</small> <small>This product is environmentally friendly and has low VOC (volatile organic compounds)</small>	Cleaning	-Clean all equipments with water. Spray equipment should be given a final rinse with white spirit to prevent rusting
	Volatile Organic Compounds (VOC)	- < 30 gms/ltr

Surface Preparation

All surfaces to be painted must be clean, dry and free from dusts, grease or any loose material.

New Unpainted Cement or Plaster surfaces:

No priming is required when coating new or unpainted plaster, cement rendering, fair faced concrete, brick stone etc. Surface to be painted must be clean, dry and free from grease and other impurities. 3 coats are recommended allowing 4 hours between coats.

Previously painted surface :

If the existing paint work is in good condition, then the surface should be cleaned, rubbed down and 2-3 coats of Duracoat Duraplast applied.

Brick and Asbestos Surfaces :

These should be sealed with one coat Duracoat Acrylic Sealer to reduce absorption followed by 2-3 coats of Duracoat Duraplast.

Precautions

- Ensure good ventilation during application and drying
- Store the product at ambient conditions in well ventilated locations and away from the source of ignition and fire
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persists seek medical advise
- Do not inhale or inject. In case of inhalation move to fresh air and seek medication attention if symptoms persists in both the cases.
- Use appropriate personal protective equipments.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould, etc before application of the paint system.

Application

- Stir thoroughly before and during use
- Always use good quality brush
- Try to paint in one motion
- Always pre test on a small area first

Note

- When over coating a dark shade with a light shade three coats may be required
- On dark shades like bright Reds, Greens, Oranges an additional coat will be required as some shades have low opacity

Post Application Instructions

For removing stains, sponge clean with mild soap solution and wipe clean. Ensure a drying of 1 week before cleaning.

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

Refer to MSDS for additional health and safety information

Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. representative to obtain the most recent Product Data Information