

## Duracoat Vinyl Matt Deluxe Emulsion

### Features

- 5 years warranty
- Excellent outdoor durability
- Does not retain dirt
- Provides a mildew resistant coating
- Excellent adhesion
- Outstanding protection against UV rays
- Long lasting fresh appearance
- Self Priming

### General Description

New improved formula based on advanced pure acrylic binder technology which provides long lasting matt finish with excellent resistance to dirt pick up. Duracoat Vinyl Matt Deluxe Emulsion is suitable for new and previously painted surfaces on cement plaster, brick, ceilings, hardboards, softboards etc.


### Recommended for

Interior / exterior residential & commercial applications where matt finish with highest performance characteristics are desired.

### Limitations

Do not apply when air and surface temperatures are below 10°C and above 35°C.

### Product Information

<b>Colour Range :</b> Available in a wide range of colors from Duracoat Color Chart, Duracoat Classic Fandek and Duracoat Color Plus Fandek	<b>Technical Data</b>	
	<b>Finish</b>	Matt
<b>Special Colors :</b> Special colors can be made available on request	<b>Spread Rate</b>	12-14 m <sup>2</sup> /l when applied on a smooth plaster
	<b>Drying time</b> - Surface dry - Recoating time	20-30 mins 3 hours
<b>Pack sizes :</b> 1ltr, 4 ltrs, 20 ltrs	<b>Application</b>	By Brush, Rollers, Conventional Spray
<b>Technical Assistance:</b> If in doubt please contact our Technical department on 6823555/954	<b>Thinning</b>	Up to 30% (Vol.) water if applied by brush or roller. If applied by spray, more water may be needed to adjust to spray able viscosity.
 <p><b>DuraCoat</b>   <b>ECO FRIENDLY PAINT</b>                  ASK THE EXPERTS                  This product is environmentally friendly and has low VOC (volatile organic compounds)</p>	<b>Cleaning</b>	Clean all equipments with water. Spray equipment should be given a final rinse with white spirit to prevent rusting
	<b>Volatile Organic Compounds (VOC)</b>	< 30 gm/l

## Duracoat Vinyl Matt Deluxe Emulsion

### Surface Preparation

All surfaces to be painted must be clean, dry and free from dusts, grease or any loose material.

#### **New Unpainted Cement or Plaster surfaces:**

If the surface is dry and absorbent, apply one coat of Duracoat Alkali Resistant Primer or Duracoat Universal undercoat. Follow up with 2-3 coats of Duracoat Vinyl Matt Deluxe Emulsion with recommended thinning.

#### **Previously painted surface :**

If the existing paint work is in good condition, then the surface should be cleaned, rubbed down and 2-3 coats of Duracoat Vinyl Matt Deluxe Emulsion applied.

#### **Brick and Asbestos Surfaces :**

These should be sealed with one coat of Duracoat Acrylic Sealer to reduce absorption followed by 2-3 coats of Duracoat Vinyl Matt Deluxe Emulsion Paint.

### Precautions

- Ensure good ventilation during application and drying
- Store the product at ambient conditions in well ventilated locations and away from the source of ignition and fire
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist seek medical advice
- Do not inhale or inject. In case of inhalation move to fresh air. Seek medical attention if symptoms persist in both the cases.
- Use appropriate personal protective equipments.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould, etc before application of the paint system.

### Application

- Stir thoroughly before and during use
- Always use good quality brush
- Try to paint in one motion
- Always pre test on a small area first

### Note

- When over coating a dark shade with a light shade three coats may be required
- On dark shades like bright Reds, Greens, Oranges, Yellow an additional coat will be required as some shades have low opacity

### Post Application Instructions

For removing stains, sponge clean with mild soap solution and wipe clean. Ensure a drying of 1 week before cleaning.

**KEEP OUT OF REACH OF CHILDREN  
PROTECT FROM FREEZING**

**Refer to MSDS for additional health and safety information**

### Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. representative to obtain the most recent Product Data Information

Basco Products (K) Ltd. P.O. Box 34424-00100, North Airport Road, Embakasi, Nairobi, Kenya  
Tel:+254-20-6823555/954, Fax: +254-20-6823956 [www.bascopaints.com](http://www.bascopaints.com)